

19



Europäisches Patentamt
European Patent Office
Office européen des brevets

11

Publication number:

**0 049 958
B1**

12

EUROPEAN PATENT SPECIFICATION

45

Date of publication of patent specification: **05.11.86**

51

Int. Cl.⁴: **A 62 D 1/02**

21

Application number: **81304265.2**

22

Date of filing: **17.09.81**

54

Fire-fighting compositions.

30

Priority: **30.09.80 GB 8031466**

43

Date of publication of application:
21.04.82 Bulletin 82/16

45

Publication of the grant of the patent:
05.11.86 Bulletin 86/45

84

Designated Contracting States:
BE DE FR GB IT SE

50

References cited:
**CA-A- 814 905
FR-A-2 308 674
GB-A-1 245 124
GB-A-1 280 508
GB-A-1 355 601
GB-A-1 566 724**

73

Proprietor: **ANGUS FIRE ARMOUR LIMITED**
Thame Park Road
Thame Oxfordshire OX9 3RQ (GB)

72

Inventor: **Mulligan, David John**
Retford House Robin Lane
Bentham Lancaster (GB)

74

Representative: **Pennant, Pyers et al**
Stevens, Hewlett & Perkins 5 Quality Court
Chancery Lane
London, WC2A 1HZ (GB)

EP 0 049 958 B1

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European patent convention).

Courier Press, Leamington Spa, England.

Description

This invention relates to fire-fighting compositions and particularly to compositions for use in preventing or inhibiting the release of flammable vapours from liquids and for use in combating fires on flammable liquids.

Foamable fire-fighting compositions based on an aqueous blend of a fluorosurfactant and a hydrolysed protein, so-called "fluoroprotein" compositions, are known. The best fluoroprotein compositions available commercially prior to the present invention provide superior security against re-ignition but have inferior flame extinction, i.e. knock down, when compared to aqueous film-forming foams based on synthetic surfactants, particularly fluorosurfactants, known as "AFFF" compositions. The best commercially available AFFF compositions, on the other hand, have superior knockdown properties and provide vapour securing films on most flammable fuels but have inferior post-extinction security, especially on hot fires, when compared to the best fluoroprotein compositions. Thus, fluoroprotein compositions were preferred for some fire situations and AFFF compositions for others.

British Patent Specification 1566724 describes film-forming fire-fighting compositions comprising a mixture of fluorosurfactant and fluorine-free surfactant. The fluorine-free surfactant is stated to be essential in order to achieve film-forming properties. The possibility of including proteinateous foam-forming liquid is briefly and tentatively mentioned.


Canadian Patent Specification 814905 describes a fluoroprotein fire-fighting composition which is characterized by having good heat resistance. It is believed that the compositions described would not be film-forming.

British Patent Specification 1280508 describes a film-forming fire-fighting composition including fluoro-surfactant, fluorine-free surfactant and protein foam material. It is emphasised that the fluorine-free surfactant is essential in order to achieve film-forming properties.

British Patent Specification 1245124 describes a fluoroprotein fire-fighting composition having good heat resistance. The compositions described would not be film-forming.

It is now discovered that, by a particular selection of fluorosurfactant, a fluoroprotein composition can be produced which possesses the superior properties of both the known fluoroprotein compositions and the AFFF compositions.


According to the present invention, therefore, there is provided a fire-fighting film-forming composition which comprises in an aqueous medium a blend of a hydrolysed protein and an ampholytic sulphonamide fluorosurfactant falling within the general formula:—




said fluorosurfactant, when as a 0.1% aqueous solution, being film-forming on cyclohexane at normal temperatures, fluorine-free surfactants being substantially absent.

The particularly preferred fluorosurfactant for employment in the present invention is that available under the trade name Forafac 1157 which is a 27% active (solids) solution of fluorosurfactant in 50/50 methanol/water. The usefulness of this fluorosurfactant is particularly surprising since the fluorosurfactant available under the trade name Forafac 1116, which has a very similar chemical formula to that of Forafac 1157, is not suitable for use in the present invention.

The fluorosurfactant of Forafac 1116 is believed to have the formula:—



When in the form of a 0.1% aqueous solution this fluorosurfactant does not form a film on cyclohexane at normal temperatures (such as 10—25°C). In contrast, a 0.1% aqueous solution of the fluorosurfactant of Forafac 1157 does form a film on cyclohexane at normal temperatures. It is found also that the storage stability of fluoroprotein compositions based on Forafac 1116 is significantly inferior to that of fluoroprotein compositions based on Forafac 1157. The formula of the fluorosurfactant in Forafac 1157 is believed to be:—



The amount of fluorosurfactant in the composition as applied to a flammable liquid is preferably at least 0.015 part by weight per 100 parts by weight of the composition. The upper limit on the amount of fluorosurfactant is dependant mainly on economical and practical considerations. A suitable upper limit is 0.15 part by weight of fluorosurfactant per 100 parts by weight of the composition. Usually the composition is stored in concentrated form and is diluted with water, and usually foamed, immediately prior to application to a fire. For instance, the amount of Forafac 1157 in the concentrate is preferably from 1.5 to 10

parts by weight per 100 parts by weight of concentrate. However, if an additional surfactant is present in the composition, the amount of the fluorosurfactant as defined above may be reduced.

Hydrolysed proteins for use in fire-fighting compositions are well known. They are made by hydrolysing substances such as keratins and albumens which are found in animal hooves, horns, feathers and blood. They are employed as aqueous compositions (bases) which often contain one or more additives such as stabilisers, preservatives and complexing agents, e.g. iron salts, zinc salts, sodium citrate and sodium chloride, all of which are known additives to improve solution-stability and fire-fighting properties such as foam-stability, heat-resistance and foam-drainage.

The hydrolysed protein bases employed in the present invention usually have a pH of less than 9, e.g. from 6 to 8. The amount of hydrolysed protein present in the composition as applied to a fire suitably is in the range of from 0.3 to 3.0 parts by weight (solids) per 100 parts by weight of the composition. In the concentrate form of the composition the amount of hydrolysed protein base present may be, for example, from 30 to 90 per cent by weight of the concentrate, and the concentration of hydrolysed protein in the hydrolysed protein base may be, for example, from 20 to 25% weight/volume in a 6% concentrate, and from 35 to 45% weight/volume in a 3% concentrate. By 6% and 3% concentrates is meant that the concentrates are formulated for dilution with 94 and 97 parts by volume of water, respectively, to produce the composition to be applied to a fire.

The composition of the invention is film-forming, i.e. it passes the film-formation test on cyclohexane at room temperature as described in U S Military Specification MIL—F—24385B dated 25 May 1978.

It is found that the interfacial tension between the composition and the flammable liquid to which it is applied is particularly important. It is found that the composition preferably should have a minimum interfacial tension of 3.5 mNm^{-1} on standard United Kingdom 4-star petrol (British Standard Specification 4040 of 1978) having a surface tension of $20 \pm 0.5 \text{ mNm}^{-1}$. It is found that below this level the applied composition, particularly when in foam form, is contaminated by the flammable liquid to such an extent that the fire-fighting properties of the compositions are diminished to an unacceptable level. Accordingly fluorine-free surfactants (also known as hydrocarbon surfactants) are substantially absent from the composition since such surfactants usually result in an undesirable reduction of interfacial tension. By "substantially absent" there is meant the absence of an amount sufficient to affect significantly the fire-fighting properties of the composition (e.g. film-formation, flame knockdown, burnback resistance or foam drainage rate). Preferably the composition is completely free of fluorine-free surfactant.

The composition preferably contains a foam booster. A preferred foam booster is hexylene glycol but other examples of foam boosters are isopropyl alcohol, butyl carbitol (butyl glycol or butyl oxitol) and butyl cellosolve. A suitable range of proportions of foam booster in the composition is from 2 to 40, especially from 2 to 15, parts by weight per 100 parts by weight of hydrolysed protein. Cellosolve is a Trade Mark.

When the composition is for use in hydrophilic polar solvents such as alcohols and ketones, preferably it includes a hydrophilic polymeric foam-stabiliser such as a polysaccharide, especially an anionic heteropolysaccharide such as a xanthan gum having a high molecular weight, e.g. that sold under the Trade Mark Actigum CX9. Usually such a polysaccharide improves the stability of the foam and thereby decreases the drainage rate. Only a small amount is required to confer a noticeable change in properties, e.g. an amount of less than 1% by weight based on the composition as applied to the flammable solvent may be employed.

Other ingredients which are usually employed in fire-fighting compositions may be employed in the composition of the invention. Examples of such ingredients are freezing point depressants such as ethylene glycol and preservatives such as that available under the trade name Glokill.

The amount of water present in the composition should be sufficient to dissolve at least the normally solid ingredients of the composition and usually the only water present in the concentrate form of the composition is that of the hydrolysed protein base and possibly also that of the commercially obtained fluorosurfactant solution.

The composition of the present invention is employed in the usual way to prevent or inhibit the release of flammable vapours or to combat fires on flammable liquids. The composition is particularly suitable for application in the form of a foam. Usually it is stored in the form of an aqueous concentrate requiring only dilution with water (to form the "pre-mix") and aeration to produce a foam which is applied to the flammable liquid surface. It is suitable for dilution with either fresh or sea water.

The typical composition as applied is compatible with conventional fire-fighting foam compositions and with conventional dry powder fire-extinguishing agents and is suitable for application by twin-agent appliances. It can be applied by standard low- and medium-expansion foam-generating apparatuses. It is suitable for application by hand-held and fixed spray-appliances and, as a result of its high resistance to contamination by flammable liquid hydrocarbon fuels and good foam stability, it can be applied to such fuels by injection of the foamed composition into the base of the fuel container. Thus it is acceptable for use in a wide range of fire situations.

The invention is illustrated in the following Examples, in which all "parts" are by volume unless otherwise stated.

0 049 958

Example I

The following compositions were prepared.

5		Parts	
		A	B
	Forafac 1157 (27% active)	0	3.3
	Forafac 1116 (40% active)	2.5	0
10	Butyl oxitol	10	10
	Hydrolysed protein base	80	80
15	Added water	7.5	6.7
		100	100

The amounts of the Forafacs are sufficient to provide a 0.9% concentration of the active fluorosurfactant in the total composition.

The fire performances of these 6% pre-mixes were tested on Avgas according to the United Kingdom Government Defence Specification DEF 42—24. The results were as follows.

25		A	B
	Foam expansion (%)	9.8	10.0
	25% drainage time (min)	5.3	4.75
30	Foam cover (sec)	24	25
	90% control of fire (sec)	34	30
	Extinction time (sec)	60	40
35	Burnback time (min)	9.9	10.9

The film-formation of each of these 6% pre-mix compositions was tested by placing a spot of the composition carefully on the surface of various hydrocarbon fuels at room temperature. The results were as follows.

45		A	B
	Cyclohexane	No film	Pronounced film
	4-Star petrol (S.T. = $20 \pm 0.5 \text{ mNm}^{-1}$)	Very slight film	Pronounced film
	Avgas	No film	Very slight film
50	Avtur	No film	Pronounced film

Both compositions had interfacial tensions of more than 4 mNm^{-1} on standard United Kingdom 4-star petrol having a surface tension of $20 \pm 0.5 \text{ mNm}^{-1}$. However, as can be seen from the above results, the composition containing Forafac 1157 was film-forming but the composition containing Forafac 1116 was not.

Example II

The following compositions were prepared.

		Parts	
		C	D
5			
10	Forafac 1157 (27% active)	0	2.7
	Forafac 1116 (40% active)	2.0	0
	Hexylene glycol	10	10
15	Actigum CX9	0.75	0.75
	Hydrolysed protein liquor	57	57
20	Added water	30.25	29.55
		100	100

The parts of Actigum CX9 are by weight.

The amounts of the Forafacs are such that the same amount (0.73%) of active fluorosurfactant is present in each formulation.

Both compositions had interfacial tensions of more than 4 mNm^{-1} on standard United Kingdom 4-star petrol having a surface tension of $20 \pm 0.5 \text{ mNm}^{-1}$.

The following properties were exhibited before and after storage for 12 days at 60°C .

		C		D	
		initial	12 days	initial	12 days
30					
35	Foam expansion (%)	8.2	3.7	8.0	8.7
	25% drainage time (min)	4.8	3.3	4.75	5.0

These results show the very good storage stability of the Forafac 1157 composition in contrast to the poor storage stability of the Forafac 1116 composition.

Example III

Two concentrates were made according to the following formulations:—

		Parts	
		E	F
45			
50	Forafac 1157 (27% solids)	3.5	3.5
	Fluorine-free surfactant (30% solids)	0	3
	Hydrolysed protein base (34% solids)	96.5	93.5

The fluorine-free surfactant was an alkyl amido propyl dimethyl amine betaine sold under the trade name Empigen BT.

The two concentrates were tested as solutions containing 6 parts of concentrate to 94 parts of water according to the following procedure.

9 litres of standard United Kingdom 4-star petrol having a surface tension of $20 \pm 0.5 \text{ mNm}^{-1}$ were placed in a 0.25 m^2 round fire tray and ignited. After 60 seconds a foam branchpipe delivering 2.25 litres per minute of solution was directed at the centre of the fire for one minute.

The results are shown below:—

	E	F
5	Fire extinguished 7 seconds after terminating foam application	Fire not extinguished and foam burnt to complete destruction

The test was repeated without lighting the petrol, and foam and solution samples were collected for analysis, yielding the following results:—

	E	F
10	Interfacial tension mNm^{-1}	4.9
15	Petrol in foam sample (%)	11
		42

The action of the fluorine-free surfactant was to reduce interfacial tension, increase fuel contamination, and thus to impair fire performance.

Example IV
A concentrate was made up according to the following formulation:—

	G
25	Forafac 1157 (27% solids)
	4 parts
	Hydrolysed protein base (34% solids)
	96 parts

Two controlled-discharge foam extinguishers were each filled with 10 litres of solution made from 1 part of concentrate plus 9 parts of water.

450 litres of aviation grade kerosene (Avtur) were poured into a 37 m² square bund containing a water base and were ignited. When the fuel was fully involved in flames the fire was tackled by two operators with the two extinguishers, spreading the foam as widely as possible on the fire. The fire was fully extinguished in 70 seconds, at the exceptionally low foam application rate of 0.5 l/m²/min.

Example V

2250 litres of aviation grade kerosene (Avtur) were placed in an 81 m² bund on a water base and ignited. After 60 seconds of burning, a solution made from 6 parts of concentrate G to 94 parts of water was applied as a foam spray to the fire by an operator using a portable branchpipe delivering 160 litres of solution per minute. The fire was fought in an aggressive manner, spreading the foam as widely as possible.


The results of this test are shown below in comparison with typical data for synthetic aqueous film-forming foam (AFFF) in this test.

	G	AFFF
45	Fire control time (sec.)	15
	Fire extinction time (sec.)	20
		18
		24

Concentrate G showed a clear superiority over AFFF in this severe fire test which simulates an aircraft crash situation.

Claims


1. A fire-fighting composition which comprises in an aqueous medium a blend of a hydrolysed protein and a fluorosurfactant which is an ampholytic sulphonamide fluorosurfactant falling within the general formula:—



said fluorosurfactant, when as a 0.1% aqueous solution, being film-forming on cyclohexane at normal temperatures, characterized in that the fire-fighting composition is film-forming and in that fluorine-free surfactants are substantially absent.

2. A composition according to claim 1 characterised in that the amount of the fluorosurfactant in the composition in concentrate form is from 1.5 to 10 parts by weight per 100 parts by weight of concentrate.

3. A composition according to claim 1 or claim 2 characterized in that the fluorosurfactant has the formula:—



4. A composition according to any preceding claim characterised by having a minimum interfacial tension of 3.5 mNm^{-1} on standard United Kingdom 4-star petrol having a surface tension of $20\text{--}0.5 \text{ mNm}^{-1}$.

5. A composition according to any preceding claim characterised in that the amount of the fluorosurfactant present in the composition for application to a flammable liquid is at least 0.015 part by weight per 100 parts by weight of the composition.

6. A composition according to any preceding claim characterised in that the amount of the fluorosurfactant in the composition for application to a flammable liquid is up to 0.15 part by weight per 100 parts by weight of the composition.

7. A composition according to any preceding claim characterised in that the amount of the hydrolysed protein in the composition for application to a flammable liquid is from 0.3 to 3.0 parts by weight (solids) per 100 parts by weight of the composition.

8. A composition according to any preceding claim characterised in that the amount of hydrolysed protein base in the concentrate form of the composition is from 30 to 90% by weight of the concentrate.

9. A composition according to any preceding claim characterised in that it contains hexylene glycol.


10. A composition according to any preceding claim characterised in that it contains a hydrophilic polymeric foam-stabiliser which is an anionic hetero-polysaccharide such as a xanthan gum.

11. A composition according to any preceding claim characterised in that it is suitable for application in foam form to a flammable liquid.

12. A method of preventing or inhibiting the release of a flammable vapour from a liquid or combating a fire on a flammable liquid characterised by applying to the liquid surface a composition according to any preceding claim, if necessary after dilution.

30 Patentansprüche


1. Zusammensetzung zur Brandbekämpfung, die in wässrigem Medium eine Mischung aus einem hydrolysierten Protein und einem Fluor-Schaumbildner enthält, wobei der Fluor-Schaumbildner ein ampholytisches Sulfonamid der allgemeinen Formel:



ist, und wobei der Fluor-Schaumbildner, wenn er in 0,1 %-iger wässriger Lösung vorliegt, einen Film aus Cyklohexan bei normalen Temperaturen bildet, dadurch gekennzeichnet, daß die Zusammensetzung filmbildend ist und daß praktisch keine fluor-freien Schaumbildner vorhanden sind.

2. Zusammensetzung nach Anspruch 1, dadurch gekennzeichnet, daß die Menge an Fluor-Schaumbildnern in der Zusammensetzung in konzentrierter Form 1,5 bis 10 Gewichtsteile pro 100 Gewichtsteile des Konzentrates beträgt.

3. Zusammensetzung nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß der Fluor-Schaumbildner die Formel



hat.

4. Zusammensetzung nach einem der vorangehenden Ansprüche, dadurch gekennzeichnet, daß sie eine minimale Grenzflächenspannung von $3,5 \text{ mNm}^{-1}$ auf Standard United Kingdom 4-Star Petrol, das eine Oberflächenspannung von $20\pm 0,5 \text{ mNm}^{-1}$ hat, besitzt.

5. Zusammensetzung nach einem der vorangehenden Ansprüche, dadurch gekennzeichnet, daß die Menge an Fluor-Schaumbildner in der Zusammensetzung zur Anwendung bei brennbarer Flüssigkeit mindestens 0,015 Gewichtsteile pro 100 Gewichtsteile der Zusammensetzung beträgt.

6. Zusammensetzung nach einem der vorangehenden Ansprüche, dadurch gekennzeichnet, daß die Menge an Fluor-Schaumbildner in der Zusammensetzung zur Anwendung bei einer brennbaren Flüssigkeit bis zu 0,15 Gewichtsteile pro 100 Gewichtsteile der Zusammensetzung beträgt.

7. Zusammensetzung nach einem der vorangehenden Ansprüche, dadurch gekennzeichnet, daß die Menge hydrolysierten Proteins in der Zusammensetzung zur Anwendung bei einer brennbaren Flüssigkeit im Bereich von 0,3 bis 3,0 Gewichtsteile (Feststoffe) pro 100 Gewichtsteile der Zusammensetzung liegt.

8. Zusammensetzung nach einem der vorangehenden Ansprüche, dadurch gekennzeichnet, daß die Menge hydrolysierten Protein-Basis in konzentrierter Form der Zusammensetzung 30 bis 90 Gew.-% des Konzentrates beträgt.

9. Zusammensetzung nach einem der vorangehenden Ansprüche, dadurch gekennzeichnet, daß sie Hexylenglykol enthält.


10. Zusammensetzung nach einem der vorangehenden Ansprüche, dadurch gekennzeichnet, daß sie einen hydrophilen polymeren Schaum-Stabilisator enthält, der ein anionisches Heteropolysaccharid, wie z.B. Xanthan-Gum, ist.

11. Zusammensetzung nach einem der vorangehenden Ansprüche, dadurch gekennzeichnet, daß sie sich zur Anwendung in Form von Schaum bei einer brennbaren Flüssigkeit eignet.

12. Verfahren zum Vermeiden oder Verhindern des Entweichens eines brennbaren Dampfes aus einer Flüssigkeit bzw. zur Brandbekämpfung bei einer brennbaren Flüssigkeit, gekennzeichnet, durch Anwendung einer Zusammensetzung entsprechend einem der vorangehenden Ansprüche auf die Oberfläche der Flüssigkeit, wenn notwendig, nach Verdünnung.

Revendications


1. Composition pour la lutte contre les incendies, qui comprend, dans un milieu aqueux, un mélange d'une protéine hydrolysée et d'un agent tensio-actif fluoré qui est un agent tensio-actif fluoré de type sulfonamide ampholyte, entrant dans le cadre de la formule générale:



ledit agent tensio-actif fluoré, lorsqu'il se trouve sous la forme d'une solution aqueuse à 0,1%, étant filmogène sur le cyclohexane aux températures normales, caractérisée par le fait que la composition de lutte contre les incendies est filmogène et que les agents tensio-actifs exempts de fluor sont pratiquement absents.

2. Composition selon la revendication 1, caractérisée par le fait que la quantité de l'agent tensio-actif fluoré dans la composition sous la forme de concentré va de 1,5 à 10 parties en poids pour 100 parties en poids de concentré.

3. Composition selon la revendication 1 ou la revendication 2, caractérisée par le fait que l'agent tensio-actif fluoré présente la formule:



4. Composition selon l'une des revendications précédentes, caractérisée comme présentant une tension interfaciale minimale de $3,5 \text{ mNm}^{-1}$ sur de l'essence standard 4 étoiles Grande-Bretagne présentant une tension superficielle de $20 \pm 0,5 \text{ mNm}^{-1}$.

5. Composition selon l'une des revendications précédentes, caractérisée par le fait que la quantité de l'agent tensio-actif fluoré, présente dans la composition destinée à être appliquée sur un liquide inflammable, est d'au moins 0,015 partie en poids pour 100 parties de la composition.

6. Composition selon l'une des revendications précédentes, caractérisée par le fait que la quantité de l'agent tensio-actif fluoré de la composition destinée à être appliquée sur un liquide inflammable, va jusqu'à 0,15 partie en poids pour 100 parties en poids de la composition.

7. Composition selon l'une des revendications précédentes, caractérisée par le fait que la quantité de la protéine hydrolysée de la composition destinée à être appliquée sur un liquide inflammable, va de 0,3 à 3,0 parties en poids (solides) pour 100 parties en poids de la composition.

8. Composition selon l'une des revendications précédentes, caractérisée par le fait que la quantité de la base protéinique hydrolysée dans la forme concentrée de la composition, va de 30 à 90% en poids du concentré.

9. Composition selon l'une des revendications précédentes, caractérisée par le fait qu'elle contient de l'hexylène glycol.

10. Composition selon l'une des revendications précédentes, caractérisée par le fait qu'elle contient un stabilisant de mousse polymère hydrophile, qui est un hétéro-polysaccharide anionique, tel qu'une gomme de xanthane.

11. Composition selon l'une des revendications précédentes, caractérisée par le fait qu'elle est appropriée pour être appliquée sous la forme de mousse sur un liquide inflammable.

12. Procédé pour empêcher ou inhiber le dégagement d'une vapeur inflammable à partir d'un liquide ou pour combattre un incendie sur un liquide inflammable, caractérisé par l'application, sur la surface de liquide, d'une composition selon l'une des revendications précédentes, si nécessaire après dilution.